Arc Stud Welding Guns



Designed for comfortable operation, KOCO Arc Stud Welding guns are renown for their sturdiness and reliability, producing first -class welding results even under difficult operating conditions. An adjustable hydraulic plunge damper is standard in the K22-D, K24 & K26 guns to damp the stud movement when it is plunged into the welding pool (recommended for welding studs from approx. 14mm diameter.



Туре	SK14	K22	K22-D	K24	K26
Stud welding with ceramic ferrule Weldable stud range Ø (mm)	4-12	4-14	4-19	13-22	13-25
Short cycle stud welding Weldable stud range Ø (mm)	3-12	6-12	0	-	-
Stud welding with shielding gas Weldable stud range Ø (mm)	3-12	3-16	0	-	-
Adjustable hydraulic plunge damper for studs from app. 14mm Ø	1	0	•	•	•
Lifting ring system with length compensation	1	•	•	•	•
Compensation for stud length variations up to(mm)	1	8	8	8	8
Standard support withlegs	2	2	2	2	2
Lifting range from to (mm)	1-4.5	1-4.5	1-4.5	2.5-6	2.5-6
Input voltage lifting coil (V=)	60-90	60-90	60-90	60-90	60-90
Welding cable (m/mm²)	5/35	2/50	2/50	2/95	2/120
Welding cable plug (mm²)	35	50/70	50/70	95	120
Control cable (m/mm²)	5/4x1.0	2/4x1.0	2/4x1.0	2/4x1.0	2/4x1.0
Control cable plug (4 wire)	•	•	•	•	•
Body: fibre-glass reinforced polyamide (black)	•	•	•	•	•
Length (excluding chuck) (mm)	185	175	175	250	300
Body Ø approx. (mm)	50	60	60	60	63
Height (including handle) (mm)	150	165	165	220	240
Weight excluding cables app. (kg)	0.9	1.3	1.3	1.4	2.6

● = standard ○ = optional -= not available

